



RO Storage Tanks

RO Plasteel Storage Tanks

FEATURES

- Manufactured of FDA-approved materials
- Diaphragm post-cured to eliminate odors from the tank
- Discharges in a vertical or horizontal position
- Stainless Steel connector

APPLICATIONS

- POU RO Systems
- Residential & Light Commercial
- Maximum operation temp 180°F
- Maximum working pressure: 80 psi



This RO Storage Tank is Tested and Certified by NSF International against NSF/ANSI Standard 58 for materials and structural integrity requirements.

COMPONENT



RO PLASTEEL STORAGE TANKS (ROPS)

ITEM	TANK SIZE AND WATER VOLUME IN US GALLONS*			TANK DIAMETER	TANK HEIGHT	PORT SIZE	TANK COLOR
	EMPTY TANK SIZE	VOLUME AT 40 PSI	VOLUME AT 60 PSI				
UTROPS-3W	3.0	1.5	2.2	10.0"	14.9"	¼" NPT-MALE	WHITE
UTROPS-4W	4.0	2.2	3.2	11.5"	15.0"	¼" NPT-MALE	WHITE
UTROPS-5W	5.0	2.8	3.8	12.0"	16.0"	¼" NPT-MALE	WHITE

* For Reference only actual results may vary. Subject to change without notice.

United Tanks, LLC

75 Main Street Suite #1097 | Norwalk, CT 06851 | Tel: 1 (888) 893-1346
 unitedtanks.com | Manufacturing Facility: #1 UNITED TANKS