



RO Storage Tanks

RO Metal Storage Tanks

RO metal storage and bladder tanks are heavy duty and NSF listed, providing years of trouble free operations. They can be installed either vertically or horizontally. They keep water tasting fresh.

FEATURES

- Manufactured of FDA-approved materials
- Diaphragm post-cured to eliminate odors from the tank
- Discharges in a vertical or horizontal position
- Stainless Steel connector

APPLICATIONS

- POU RO Systems
- Residential & Light Commercial
- Maximum operation temp 180°F
- Maximum working pressure: 80 psi



This RO Storage Tank is Tested and Certified by NSF International against NSF/ANSI Standard 58 for materials and structural integrity requirements.

COMPONENT



RO METAL TANKS (ROM)

ITEM	TANK SIZE AND WATER VOLUME IN US GALLONS*			TANK DIAMETER	TANK HEIGHT	PORT SIZE	TANK COLOR
	EMPTY TANK SIZE	VOLUME AT 40 PSI	VOLUME AT 60 PSI				
UTROM-2WH	2.0	0.8	1.2	8.3"	13.0"	¼" NPT-MALE	WHITE
UTROM-2BL	2.0	0.8	1.2	8.3"	13.0"	¼" NPT-MALE	BLUE
UTROM-3WH	3.0	1.5	2.2	10.0"	14.9"	¼" NPT-MALE	WHITE
UTROM-3BL	3.0	1.5	2.2	10.0"	14.9"	¼" NPT-MALE	BLUE
UTROM-4WH	4.0	2.2	3.2	11.5"	15.0"	¼" NPT-MALE	WHITE
UTROM-4BL	4.0	2.2	3.2	11.5"	15.0"	¼" NPT-MALE	BLUE
UTROM-5WH	5.0	2.8	3.8	12.0"	16.0"	¼" NPT-MALE	WHITE
UTROM-5BL	5.0	2.8	3.8	12.0"	16.0"	¼" NPT-MALE	BLUE
UTROM-9WH-14	9.0	5.0	7.0	12.7"	21.5"	¼" NPT-MALE	WHITE
UTROM-9BL-14	9.0	5.0	7.0	12.7"	21.5"	¼" NPT-MALE	BLUE
UTROM-14WH-34	14.0	7.0	9.0	15.8"	25.3"	¾" NPT-MALE	WHITE
UTROM-14BL-34	14.0	7.0	9.0	15.8"	25.3"	¾" NPT-MALE	BLUE
UTROM-20WH	20.0	11.0	14.0	15.8"	32.0"	¾" NPT-MALE	WHITE
UTROM-20BL	20.0	11.0	14.0	15.8"	32.0"	¾" NPT-MALE	BLUE
UTROM-28WH	28.0	15.0	20.0	17.0"	32.0"	1" NPT-MALE	WHITE
UTROM-40WH	40.0	20.0	28.0	17.0"	42.0"	1" NPT-MALE	WHITE

* For Reference only actual results may vary. Subject to change without notice.

United Tanks, LLC

75 Main Street Suite #1097 | Norwalk, CT 06851 | Tel: 1 (888) 893-1346
 unitedtanks.com | Manufacturing Facility: #1 UNITED TANKS